## **EUROPEAN PATENT OFFICE**

## **Patent Abstracts of Japan**

**PUBLICATION NUMBER** 

57192926

**PUBLICATION DATE** 

27-11-82

**APPLICATION DATE** 

25-05-81

**APPLICATION NUMBER** 

: 56078906

APPLICANT: SEIKO EPSON CORP:

INVENTOR: AKIYAMA MASAYUKI:

INT.CL.


: G02F 1/133 G09F 9/00

TITLE

: LIQUID CRYSTAL DISPLAY DEVICE

AND ITS ORIENTATION PROCESSING

**METHOD** 



ABSTRACT :

PURPOSE: To control optional orientation of liquid crystal molecules by forming an inorganic or organic layer composed of a groove forming agent on a base plate and pressing a pressing means with projections or grooves on the layer.

CONSTITUTION: In case of the production of a liquid crystal display device, a layer 2 of groove forming agent is formed on a base plate 1 of the liquid crystal display device at first. The groove forming agent is composed of single or plural inorganic compounds such as SiO and SiO<sub>2</sub> and organic compounds such as polyvinyl alchol, polyimide, polyamide, cellulose, cellulose acetate, "Teflon," nylon, acrylate, and styrene. Then a grooved press mold 3 is pressed on the layer 2 of the image forming agent to form liquid crystal molecule arraying grooves on the layer 2, so that the liquid crystal molecules 4 are arrayed along the grooves. For a material of the press mold, metal such as Fe, Ni, Cu, and Al or inorganic materials such as glass and ceramic are used.

COPYRIGHT: (C)1982,JPO&Japio